



NOTES:

1. ALL WELDED CONNECTIONS SHALL BE $\frac{3}{16}$ " CONTINUOUS FILLET WELDS, GROUND SMOOTH.
2. ALL SHARP OR ROUGH EDGES SHALL BE GROUND SMOOTH, GRIND CORNERS TO $\frac{1}{4}$ " \pm RADIUS
3. GATE AND POSTS SHALL BE CLEANED OF ALL RUST AND CONTAMINANTS AND PAINTED WITH NEW CAT YELLOW OR APPROVED EQUIVALENT.
4. ALL END CAPS SHALL BE $\frac{1}{2}$ " A36 GRADE B MS.
5. LOCATE THE TWO CHICANE GATES SUCH THAT, WHEN CLOSED ACROSS ACCESS ROAD AND PARALLEL TO EACH OTHER, THERE IS 6-FT OF SEPARATION BETWEEN THEM. OR AS DIRECTED BY ENGINEER FOR SPECIAL CIRCUMSTANCES.
6. PROVIDE AND INSTALL UNISTRUT SIGN SUPPORT SYSTEM FOR TRAIL SIGNS AT EACH ACCESS POINT PER CDID1 STANDARD DETAIL C-9.
7. CONTRACTOR SHALL PROVIDE SPECIFIC LOCK BODY (ONE FOR EACH PIN) TO CDID #1. LOCKS SHALL BE SMALL FORMAT IC (SFC) WITH HASP LENGTH OF $1\frac{3}{4}$ " TO $2\frac{1}{2}$ ". CDID #1 WILL INSTALL CORES.

**CHICANE ACCESS GATE
STANDARD INSTALLATION DETAIL**

5/2022	add required lock info	TC	TC	ANB	ANB
9/2020	new standard	ANB	ANB	ANB	ANB
REV	ISSUE	DWG	DES	CHK	APP



DRAWING NO.
C-2
1 of 1

DATE: SEPT 2020
DESIGN: ANB
DRAWN: ANB