



**NOTES**

- 1) MARKER POSTS SHALL BE LOCATED ON TOP OF THE PIPE UNLESS DIRECTED OTHERWISE.
- 2) STEEL BRACKET SHALL BE CLEANED AND PAINTED. BEND AT 8°. INSTALLATION OF BRACKET SHALL NOT INTERFERE WITH SAFETY GRATE BUT MAY USE GRATE MOUNTING HOLES IF APPLICABLE.
- 3) MARKER POSTS SHALL BE WHITE IN COLOR.
- 4) MARKER POSTS TO BE USED AS DIRECTED BY CDID1 OR AS SHOWN ON PLANS.
- 5) MARKER POSTS ARE REQUIRED ON ALL OUTFALL PIPES PROTRUDING INTO DITCHES & DRAINAGE WAYS OWNED OR MAINTAINED BY CDID1.
- 6) INSTALLATION: TOP OF POST SHALL BE 78" ABOVE GRADE AT POINT OF INSTALLATION. THIS MAY BE ACHIEVED BY BOLTING TWO MARKERS TOGETHER. NUTS, BOLTS AND WASHERS TO BE STAINLESS STEEL.
- 7) DRILL MOUNTING HOLES TO MATCH SD-2 CULVERT SAFETY GRATE MOUNTING HOLES AND MOUNT TOGETHER IN ONE BOLT UP.

**LOCATOR POST  
STANDARD INSTALLATION DETAIL**

5-2022	revise bracket bolt up instructions	TC	TC	ANB	ANB
12-2021	revise marker mounting location	TC	TC	ANB	ANB
9-2021	revise marker height	TC	TC	ANB	ANB
7/2020	new detail	TC	ANB	ANB	ANB
REV	ISSUE	DWG	DES	CHK	APP

